

Effortless Meeting Collaboration

AZTECH IdeaFlow AZ2586-U01



Fluent Writing Experience

Enjoy smooth, precise writing on our Interactive Display with 50-point touch sensitivity for easy collaboration.



Built-in 48MP AI Camera & Microphone

Transform your meetings with the Interactive Display's 48MP AI Camera, Auto Framing, and Speaker Tracking, delivering clear visuals and focused audio for a seamless experience.



BYOM (Bring Your Own Meeting)

With our BYOM solution, you control the meeting. Simply bring your device, connect seamlessly to the interactive display, and collaborate wirelessly.



Infinite Detail

With 4K UHD anti-glare display, enjoy images of extreme detail.



Seamless Screen Mirroring

Wireless screen mirroring from various operating systems such as Android, iOS, and Windows to the display with one touch.



Scan to Transfer

Fast file transfer allows users to quickly transfer files to the display via a QR code.

SPECIFICATION - AZ2586-U01

Display

Screen size	86 inches
Backlight	DLED
Resolution	3840X2160
Brightness(cd/m ²)	400
Contrast Ratio	5000:1
Refresh Rate	60Hz
Response Time(ms)	8
Aspect Ratio	16:9
Color Support	1.07 billion
Viewing Angle	Horizontal 178°, Vertical 178°
Surface Hardness	9H (7 on the Mohs scale)
Lifespan	50000H
Display Size (mm)	1895.04 X 1065.96

Touch

Sensing Type	50-point touch(IR), 20-point write
Glass	4mm tempered glass, Anti-glare
Touch Accuracy (mm)	±1
Response Time (ms)	≤2
Recognizable object (mm)	2
Touchscreen input	Opaque objects (e.g. finger, pen, etc.)
Touch Technology	Infrared touch

Speaker

Speaker	2*20W+20W
---------	-----------

Android System

RAM	16 GB
ROM	512 GB
CPU	RK3588: 4 x Cortex-A76 based 2.4 GHz + 4 x Cortex-A55 based 1.8
OS	Android 13.0

Camera & Microphone

Pixel	48MP Android: Pixel 8MP for Photos & 8MP for Video Windows: Pixel 48MP for Photos & 12MP for Video
Microphone array	8
Pickup distance	8
Smart function	Auto Framing & Speaker Tracking

WIFI & Bluetooth

Wifi	Wi-Fi 6, supports 5 GHz/2.4 GHz
Wifi Performance	30m ² coverage, 20m transmission distance in open space
Bluetooth	5.2



SPECIFICATION – AZ2586-U01

Interface

Video Input & Output	Input : 3 x HDMI IN (4K), 1 x DP IN, 1 x VGA IN, 1 x YPbPr IN Output : 1 x DP OUT, 1 x HDMI OUT (4K)
Audio Input & Output	Input : 1 x AUDIO IN Output : 1 x EARPHONE, 1 x coaxial audio output interface (COAX)
Other Interfaces	1 x RS232, 3 x front USB 3.0, 4 x on-board USB 3.0, 2 x TOUCH USB, 2 x Type-C, 1 x TF CARD, 1 x IR IN
Network	1 x LAN OUT, 1 x LAN IN

General

System Language	26 (Simplified Chinese, Traditional Chinese, English, Japanese, Arabic, French, Spanish(ES-ES), Spanish(ES-MX), Portuguese(ES-ES), Portuguese(ES-MX), Portuguese, German, Italian, Dutch, Polish, Korean, Catalan, Galician, Vietnamese, Bulgarian, Kazakh, Russian, Ukrainian, Thai, Uzbek, Hungarian, Croatian)
Power Supply	AC 100 to 240 V, 50/60 Hz
Standby Power Consumption (W)	< 0.5
Product Dimensions (W x H x D) (mm)	1968.1 x 1188.4 x 84.8
Package Dimensions (W x H x D)(mm)	2095 x 1320 x 220
Operating Temperature	0°C to 50°C
Weight (Kg)	Net weight: 67 KG, Gross weight: 82.4 KG
Operating Humidity	10% to 90% RH (noncondensing)
Storage Temperature	-20°C to 60°C
Storage Humidity	0% to 95% RH (noncondensing)
Wall Mount Hole (mm)	800 x 400
Wall Mount ScrewT	4 x M8 screw hole
Accessories Included	1 x power cable, 2 x stylus pen, 1 x quick guide, 1 x wall mounting bracket, 1 x IR remote control

Accessories



Pluggable PC Module



BYOM Wireless Casting Dongle



Trolley Stand

