



22 Inches LED Monitor



AZTECH AZ-M22E-FSVH



True Color Display



Resolution is Up to
at 1920*1080



Wide View of Field:
178° (H) / 178° (V)



Specific
Menu Design
which is simple to operate



Adaptively
Recognize Signal



VESA Stand Bracket



Support
Multiply Language

Specification

MODEL	AZ-M22E-FSVH
PANEL	
Backlight	ELED
Panel Size	22"
Resolution	1920 × 1080
Color Support	16.7M
Brightness (cd/m²)	250
Contrast Ratio	3000:1
Response Time (ms)	20
Pixel Pitch (H × V) (mm)	0.24 × 0.24
Viewing Angle (H/V)	Horizontal 178°, Vertical 178°
Display Size (mm)	478.6 × 260.2
Refresh Rate	100 Hz



Operation Hour	24/7
Bezel Width	2.0mm (top/left/right), 22.0mm (bottom)
Color Gamut	72% NTSC
Surface Treatment	Haze 25%, 3H
LCD Technology/Panel Type	VA
INTERFACE	
Video Input	1 × VGA (MAX: 1920 × 1080@60 Hz) and 1 × HDMI (MAX: 1920 × 1080@100 Hz)
Audio Input	1 × Audio In (3.5mm Mini-Jack)
SPEAKER	
Speaker	2 × 1.5W
VESA	
VESA (mm)	100 × 100
Wall-mounted Thread	4-M4 screw hole, 10 mm Deep Thread
OSD	
Multi-Language	12 (English, German, French, Spanish, Italian, Dutch, Chinese, Japanese, Korean, Russian, Portuguese, Turkish)
GENERAL	
Input Voltage	DC 12V, 2A
Typical Power Consumption (W)	<24
Standby Power Consumption (W)	<0.5
Product Dimensions (W × H × D) (mm)	493.1 × 290.8 × 50.5 (No Pedestal) 493.1 × 378.6 × 200.0 (With Pedestal)
Package Dimensions (W × H × D) (mm)	12 (English, German, French, Spanish, Italian, Dutch, Chinese, Japanese, Korean, Russian, Portuguese, Turkish)
Multi-Language	557 × 370 × 140
Operating Temperature	0°C ~ 40 °C
Operating Humidity	10%~90% (No Condensation)
Storage Temperature	-10°C ~ 60°C
Storage Humidity	10%~90% (No Condensation)
Material	Plastic
Lifetime (h)	30000
Certifications	CE, FCC
Standard	1 × 1.5m HDMI cable, 1 × Adapter, 1 × Pedestal, 1 × Quick Guide
MTBF (h)	50000

DIMENSIONS

